


Aluminum Truck Dock Board 72 In. x 66 In. 15000 Lb. Capacity Silver

MODEL BTA-15007266

Loading Dock Equipment / Aluminum Truck Dockboards (Welded Aluminum Curbs)



PRODUCT OVERVIEW

The Aluminum truck dock board is engineered and built to maximize safety while handling heavy fork trucks and loads. Locking legs prevent movement during loading and unloading operations. Locking legs are uneven to allow the dock board to sit canted, while not in use, for easier pickup by fork trucks. Welded aluminum safety curbs prevent accidental runoffs and provide visible driving lane. When using three-wheeled fork trucks order dock board with capacity at least four-times the lifting capacity of fork truck. The width of the dock board should be at least 15 (in.) wider than the load or equipment passing between the curbs. Bend is 11 degrees and 9" from the edge and the legs are 12" from the edge. Manufactured in compliance with OSHA.

KEY FEATURES

- 100% Aluminum construction provides rugged long lasting use
- Raised-diamond tread plate dock board surface
- Welded aluminum locking legs underneath dock board
- Beveled entry and exit edges provide a smooth transition

CORE PRODUCT DATA

ASSEMBLED WEIGHT 304 lbs	ASSEMBLED SIZE 72" W x 66" L x 13.625" H	SHIP WEIGHT 304 lbs
PACKAGE 1 SIZE 72" W x 66" D x 17" H	COLOR / FINISH Silver	FREIGHT TYPE LTL Loose
AVAILABILITY Available Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.		QUICKSHIP: --

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	15000
Height Difference (in.): 8 degree/17 percent	8
Height Difference (in.): 11 degrees/19 percent	11
Bend Degree	11
Bend Distance from Edge (in.)	9
Leg Distance from Edge (in.)	12
Usable Width (in.)	65-3/4
Usable Length (in.)	66
Edge Type	Beveled
Equipped With	Welded Aluminum Locking Legs
Surface Type	Raised-Diamond Treadplate
Plate Thickness (in.)	1/2
Curb Height (in.)	2-5/8
Curb Width (in.)	3-1/8
OSHA	1910.30 (a)
ANSI	MH 30.2

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=33>