

# Steel Quick Lift DC Powered 72 In. Raised Height 125 Lb. Capacity

**MODEL PEL-100S-D3**

Ergonomic Solutions / Powered Quick Lifts



## PRODUCT OVERVIEW

The DC powered quick lift is a quiet, lightweight unit used for transport and positioning loads quickly with just the push of the button. The unit is battery operated with a high density polyethylene platform. It features a low profile design for maneuvering in narrow aisles and confined spaces. The poly casters consist of two swivel and two swivel-locking that are standard. The DC system runs with an AC on-board charger.

## KEY FEATURES

- DC powered battery is fast and quite
- White HDPE platform offers durability and aesthetics
- Chain driven platform operation provides precise positioning
- Touch-pad control allows for easy operation

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**179 lbs**

**ASSEMBLED SIZE**  
**23.5" W x 37.5625" L x 80.3125" H**

**SHIP WEIGHT**  
**245 lbs**

**PACKAGE 1 SIZE**  
**40" W x 48" D x 88" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Out of Stock - Please Contact Sales

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                               |                                  |
|-------------------------------|----------------------------------|
| Uniform Capacity (lb.)        | 125                              |
| Lowered Height (in.)          | 5-5/8                            |
| Raised Height (in.)           | 72                               |
| Caster Diameter (in.)         | 3                                |
| Caster Type                   | (2) Swivel (2) Swivel with Brake |
| Caster Material               | Poly-on-Poly                     |
| DC Voltage                    | 24                               |
| AC Charger Voltage            | 115                              |
| Horizontal Load Center (in.)  | 9                                |
| Platform Width (in.)          | 23-1/2                           |
| Platform Length (in.)         | 18-1/2                           |
| Platform Thickness (in.)      | 1/2                              |
| Lift Speed - Loaded           | 26" / sec                        |
| Lift Speed - Unloaded         | 16" / sec                        |
| Battery Depth                 | 6                                |
| Battery Width                 | 8                                |
| Battery Height                | 4                                |
| Battery Weight                | 20                               |
| Battery Freight Class         | 60                               |
| Battery NMFC Number           | 60700                            |
| Battery NMFC Description      | Gel batteries on unit            |
| Lithium Battery Configuration | C -- Contained In                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=260>